

5127382AA

Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP

May 30, 2012
15:27

C H R Y S L E R
HAZARD COMMUNICATION SHEET

199835 DRAFT PART/COMMTY CD: 05127382AA
PREPARATION DATE: 02-25-04 STNDRD: N/AV SUPPLIER: 37637 MFGR: 03500
OSHA HAZ: YES HAZWOPER HAZ: YES CONS PROD/HAZ SUB: YES

*** SECTION 01 - PRODUCT INFORMATION ***

MFG BY: PART SALES & SERVICE CHRYSLER
26311 LAWRENCE AVE CENTERLINE MI 48015
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888
DIST BY: PART SALES & SERVICE CHRYSLER
26311 LAWRENCE AVE CENTERLINE MI 48015
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888
CHRYSLER INDUSTRIAL HYGIENE: 248-512-8260 AFTER HOURS: 248-576-8888
BRAND NAME: SHELL ATF 3403-M115
MFG ID : N/AV
DESCRIPTION: FLUID-AUTOMATIC TRANSMISSION

*** SECTION 02 - INGREDIENTS ***

HAZARDOUS INGREDIENTS: PERCENT
COMM NAME / CAS NO & CHEM NAME: BY WGT OSHA ACGIH CHRYS UNITS NOTATIONS
EXISTING INGREDIENTS
DISTILLATES (PETROLEUM), SOLVENT- 60-100 W 5 5 5 MG/M3 I1 N1
064741-89-5 DISTILLATES, PETROLE L N/AP 10 10 A2
HYDROTREATED LIGHT NAPHTHENIC DIS 60-100 W 5 5 5 MG/M3 I1 N1
064742-53-6 DISTILLATES, PETROLE L N/AP 10 10 A2
DISPERSANT 10-30 W N/AV N/AV N/AV N/AV
000756-00-2C DISPERSANT
INHIBITORS, ORGANIC 10-30 W N/AV N/AV N/AV N/AV
000950-00-2C INHIBITORS, ORGANIC
GENERIC DESC: MIXTURE(S) OF THE FOLLOWING: PETROLEUM DISTILLATE(S), WAX,
ADDITIVES AND XYLENE.

*** SECTION 03 - PHYSICAL DATA ***

BOILING POINT : N/AV SOLUB IN WATER: N/AV
VAPOR PRESSURE: < 0 MM HG ATN/AV EVAP. RATE: N/AV REF: N/AV
VAPOR DENSITY : N/AV SPECIFIC GRAVITY: 0.890 AT 60 F
PH AT FULL STRENGTH: N/AV PH AT REC. DILUT: N/AV
%VOLATILE BY VOL : N/AV VOLATILE ORGANIC COMP: N/AV N/AV
ODOR THRESHOLD: N/AV PPM FOR % POPULATION
FREEZING POINT: N/AV COEFF. OF WATER/OIL DIST: N/AV
APPEARANCE & ODOR: STATE: LIQUID..... COLOR: RED..... ODOR: HYDROCARBON.....
ODOR: PETROLEUM.....

Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP

May 30, 2012
15:27

*** SECTION 04 - FIRE AND EXPLOSION DATA ***

FLASH POINT: 374 F COC IGN TEMP: N/AV LEL: N/AV UEL: N/AV

SPECIAL FIRE & EXPLOSION HAZARDS:

PRODUCT WILL FLOAT AND CAN BE REIGNITED ON SURFACE OF WATER. DO NOT USE WATER IN STRAIGHT STREAMS.

EXTINGUISHING MEDIA:

WATER FOG, FOAM, DRY CHEMICAL OR CARBON DIOXIDE.

SPECIAL FIREFIGHTING PROCEDURES:

USE PROTECTIVE CLOTHING. USE SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE. USE WATER TO COOL FIRE EXPOSED CONTAINERS.

SENSITIVE TO MECHANICAL IMPACT?: N/AV SENSITIVE TO STATIC DISCHARGE?: N/AV

HAZARDOUS COMBUSTION PRODUCTS:

OXIDES OF NITROGEN, OXIDES OF SULFUR, OXIDES OF PHOSPHORUS, ORGANIC COMPOUNDS, CARBON MONOXIDE AND CARBON DIOXIDE.

FLAME PROJECTION: N/AP

*** SECTION 05 - HEALTH HAZARD DATA ***

EFFECTS OF OVEREXPOSURE - ACUTE & CHRONIC:

<<---EYE CONTACT--->> MINOR IRRITATION. <<---SKIN CONTACT--->> DIRECT CONTACT MAY PRODUCE THE FOLLOWING: MINOR IRRITATION.. PROLONGED CONTACT MAY PRODUCE THE FOLLOWING: OIL ACNE, FOLLICULITIS OR DERMATITIS.

<<---INHALATION--->> IF HEATED TO HIGH TEMPERATURE VAPOR MAY PRODUCE THE FOLLOWING: IRRITATION OF UPPER RESPIRATORY TRACT. <<---INGESTION--->> NO KNOWN EFFECTS. HOWEVER, INGESTION IS NOT RECOMMENDED. <<---MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY THIS PRODUCT--->> SKIN DISORDERS AND LUNG OR RESPIRATORY TRACT DISORDERS.

EMERGENCY FIRST AID PROCEDURES:

<<---EYE CONTACT--->> RINSE EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER, OCCASIONALLY LIFTING BOTH UPPER AND LOWER LIDS. CONTINUE FOR 15 MINUTES. CONTACT A PHYSICIAN. <<---SKIN CONTACT--->> REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF CONDITION PERSISTS, CONSULT A PHYSICIAN. <<---INHALATION--->> REMOVE TO FRESH AIR AT ONCE. ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. CARDIAC RESUSCITATION IF INDICATED. CONTACT A PHYSICIAN. <<---INGESTION--->> LARGE QUANTITIES-DO NOT INDUCE VOMITING-CALL PHYSICIAN IMMEDIATELY.

*** SECTION 06 - REACTIVITY DATA ***

STABILITY: STABLE

CONDITIONS TO AVOID:

HIGH TEMPERATURE AND SPARKS OR OPEN FLAME.

MATERIALS TO AVOID:

OXIDIZABLE MATERIALS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP

May 30, 2012
15:27

POLYMERIZATION CONDITIONS TO AVOID:

POLYMERIZATION WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION PRODUCTS:

OXIDES OF NITROGEN, OXIDES OF SULFUR, OXIDES OF PHOSPHORUS, ORGANIC
COMPOUNDS, CARBON MONOXIDE AND CARBON DIOXIDE.

*** SECTION 07 - SPILL OR LEAK PROCEDURES ***

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

LARGE SPILL-DO NOT FLUSH INTO SEWER SYSTEM. WEAR PROTECTIVE CLOTHING. WEAR
RESPIRATORY PROTECTION. STOP SPILL AT SOURCE. CONTAIN WITH DIKE. REMOVE
SPILL BY USING A VACUUM TRUCK. PUMP INTO SALVAGE TANK. PREVENT GROUNDWATER
CONTAMINATION. RESIDUE-ABSORB ON SAND OR VERMICULITE FLUSH AREA WITH WATER.

WASTE DISPOSAL METHODS:

DISPOSE OF IN A MANNER CONSISTENT WITH STATE, PROVINCIAL, LOCAL, AND
FEDERAL DISPOSAL REGULATIONS. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR
MAY ENTER SEWERS, WATERCOURSES OR EXTENSIVE LAND AREAS.

*** SECTION 08 - SPECIAL PROTECTION ***

RESPIRATORY PROTECTION:

ORGANIC VAPOR RESPIRATOR OR AIR-SUPPLIED RESPIRATOR. THIS EQUIPMENT MAY BE
NEEDED IF SIGNIFICANT VAPORS OR MIST ARE GENERATED.

VENTILATION TYPE:

GOOD GENERAL VENTILATION.

PROTECTIVE GLOVES:

RECOMMENDED. NITRILE RUBBER GLOVES.

EYE PROTECTION:

RECOMMENDED. CHEMICAL GOGGLES.

OTHER PROTECTIVE EQUIPMENT:

CLOTHING (SAME MATERIAL AS GLOVES). ALL SKIN CONTACT MUST BE AVOIDED.
PROTECTIVE EQUIPMENT MUST BE WORN AT ALL TIMES DURING PRODUCT USE IF SKIN
CONTACT IS POSSIBLE.

*** SECTION 09 - SPECIAL PRECAUTIONS ***

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE:

AVOID SKIN CONTACT. REMOVE CONTAMINATED CLOTHING AND LAUNDRY BEFORE REUSE.
WASH THOROUGHLY AFTER HANDLING. LEATHER CLOTHING AND SHOES WILL BE DAMAGED
BY THIS PRODUCT. STORE IN A COOL, DRY PLACE. STORE IN A WELL VENTILATED
AREA. KEEP AWAY FROM OPEN FLAME. AVOID USING OR STORING AT HIGH
TEMPERATURES.

OTHER PRECAUTIONARY MEASURES:

MAINTAIN GOOD HOUSEKEEPING AND HYGIENIC PRACTICES.

*** SECTION 10 - WASTE LABELING INFORMATION ***

60175000
s81433c

Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP

May 30, 2012
15:27

DOT LABELING INFORMATION (49 CFR 100-199)

ID#: N/AP ERG#: HAZARD CLASS - PRMY: N/AP PACKING GROUP: N/AP

NOT HAZARDOUS PER DOT REGULATIONS

RCRA INFORMATION (40 CFR 122-124, 260-265)

INFORMATION UNAVAILABLE AT THIS TIME